



PARTICULATE-BLOCKING HOODS



INNOTEX® GRAY PARTICULATE-BLOCKING HOODS: SHIELD YOURSELF FROM CONTAMINANTS.

TOXIC MICROSCOPIC CARCINOGENIC PARTICLES CAN TRAVEL THROUGH TRADITIONAL KNITTED HOODS.

When you set foot on the scene of a fire, you immediately come in contact with microscopic carcinogenic particles generated by burning materials. While we know that breathing in these cancer-causing particulates is dangerous, studies show that absorption of such toxins through the skin is just as harmful.

Unseen and imperceptible, these toxic microscopic particulates can travel through traditional knitted hoods and accumulate on your skin, especially on the highly absorptive areas of the neck, jaw and throat. As a firefighter, you face intense heat and work up a sweat. All this heat opens up skin pores, increasing its ability to absorb toxins.

Traditional hoods were designed to protect against heat, not carcinogenic particles. Today's particulate-blocking hoods are of paramount importance and a vital investment in your continued health and safety.



FOR EVERY 5-DEGREE INCREASE IN SKIN TEMPERATURE, CONTAMINATION RISK INCREASES BY 400%.

Following the lungs, the skin is the body's second largest organ by surface area, and is highly absorptive.

Some areas of skin are more permeable than others, specifically the face, the angle of the jaw, the neck and throat. Skin's permeability increases with temperature.

As you get hot, the pores open up, the absorption capacity of the skin increases. The higher the temperature, the more permeable your skin becomes. For every 5-degree increase in skin temperature, absorption and the risk of contamination increase by 400%¹.

FIREFIGHTER CANCER QUICK FACTS

Research shows that firefighters have higher cancer risks than the general population, and their risks are significantly higher for some specific cancers.

9%

Firefighters have a 9% higher risk of being diagnosed with cancer than the general population.

14%

Firefighters have a 14% higher risk of dying from cancer than the general population.

51%²

Cancer has caused 61% of career firefighter line-of-duty deaths since 2002. Heart disease caused 18% of the line-of-duty deaths.

Firefighter Cancer Support Network
AFF date 1.1.2002 to 3.31.2017





FULL COVERAGE

STEDAIR® PREVENT particulate-blocking barrier throughout the entire hood.

EXTRA-LONG 24" LENGTH

Provides complete chest and shoulder coverage. Ensures your hood stays securely tucked in, preventing particulate entry at the coat-to-neck interface.

3 MULTI-PANEL DESIGN

Ensures a snug fit and proper seal with your SCBA, no matter the head movement, even tilted backward.

FR VISCOSE LINER

Provides a soft, cool feeling on your skin and boasts excellent moisture-wicking properties to keep you drier and more comfortable.

HEAVY-DUTY 1/2" ELASTIC SEWN INTO FACE OPENING

Ensures a snug fit and proper seal with your SCBA even when you move your head. Stretches for easy donning without ever losing its shape.

FLATLOCK SEAMS

Stronger yet low-profile, ensure a more comfortable fit. Sewn with spun Nomex thread for optimal quality.

FR KNIT

Form-fitting knit allows a comfortable fit that conforms to the contours of your head.

ULTIMATE COMFORT. ULTIMATE PROTECTION.



BLOCKS MORE THAN 99.9% OF PARTICLES

STEDAIR® PREVENT particulate barrier blocks more than 99.9% of particles as small as 0.1 to 1.0 microns



AIR PERMEABLE

Allows clean air to flow through and lets moisture escape efficiently to help reduce the risk of heat stress.



SUPERIOR COMFORT

Lightweight and ergonomically-designed to ensure a comfortable fit. Inner multi-filament FR viscose liner provides a soft, cool feeling on your skin and boasts excellent moisture-wicking properties.



QUIET

Won't make crackling noises that affect your situational awareness and limit your ability to communicate.



DURABLE

Maintains its particulateblocking effectiveness even after 100 washes. Face opening retains its snug fit to prevent ingress of harmful particulates.



YOUR CHOICE: HIGHER THL.

Because everyone has different needs when it comes to thermal protection and breathability,

we've developed 2 models, one featuring our exclusive Dual Metabolic Zone design. Choose the **GRAY 25** hood for enhanced heat stress control or the **GRAY 35** hood for optimal thermal protection in critical areas.

INNOTEX® GRAY™ **TPP** 22 22* As received As received +THLAfter 5 washes 34 After 5 washes 25 ** THL 427 THL 437 SINGLE METABOLIC ZONE DESIGN **20% NOMEX** 20% PBI Effective heat stress relief 80% LENZING 80% LENZING without compromising thermal protection. 2-LAYER HOOD • **ONE** FR knit outer layer. • ONE inner layer : INNOTEX® Trilaminate with STEDAIR® PREVENT throughout. ESTED AT PBI® LAB. * NOMINAL VALUES ONE layer INNOTEX® GRAY™ **TPP** 36 As received As received After 5 washes 47 After 5 washes 34 + T P P THL 329 THL 350 **DUAL METABOLIC ZONE DESIGN** 20% NOMEX 20% PBI Higher thermal and flashover protection **80% LENZING** 80% LENZING only where you need it most. 3-LAYER HOOD • TWO FR knit outer layers in critical areas • **ONE** inner layer : INNOTEX® Trilaminate with STEDAIR® PREVENT throughout.

FABRIC PERFORMANCE.

INNOTEX® GRAY® 25/35 HOOD PERFORMANCE VALUES

			INNOTEX® GRAY™ HOOD25		INNOTEX® GRAY® HOOD35	
		Requirements NFPA 1971 / 2018 edition	20% NOMEX 80% LENZING	20% PBI 80% LENZING	20% NOMEX 80% LENZING	20% PBI 80% LENZING
PARTICULATE-BLOCKING EFFICIENCY	As received After 10 washes	0.10mm part. size ≥ 90%	99.9% 99.8%	99.6% 99.3%	99.9% 99.8%	99.6% 99.3%
THERMAL PROTECTIVE PERFORMANCE (TPP)	As received After 5 washes	≥ 20 ≥ 20	22.6 34.1	22.37 * 25 **	36.7 47.2	38.6 34.8
TOTAL HEAT LOSS (THL)	As received	≥ 325 W/m2	427	437	329	350
AFTER FLAME (Wales X Courses / sec)	As received After 5 washes	≤2.0	0 0	0	0	0
CHAR LENGTH (Wales X Courses / mm)	As received After 5 washes	≤ 2.0	23 x 18 18 x 16	20 x 28 30 x 28	23 x 18 18 x 16	20 x 28 30 x 28
HEAT & THERMAL SHRINKAGE RESISTANCE (%)	As received After 5 washes	≤ 10%	M/L -0.5 % XL -0.3 % M/L -0.5 % XL -0.5 %	M/L -0.8 % XL -1.5 % M/L -1.4 % XL -1.6 %	M/L -0.2 % XL 0% M/L -0.2 % XL -0.3 %	M/L 0 % XL 0 % M/L 0 % XL 0.2 %
CLEANING SHRINKAGE RESISTANCE (%)	Finished hood	≥ 5%	M/L -1 % XL -1.6 %	M/L -1 % XL -1.6 %	M/L -1% XL -1%	M/L 0 % XL -2.0%
FABRIC BURST STRENGTH	Knit Stedair Prevent	≥ 225 N	480 546	345 546	480 546	345 546

FABRIC PERFORMANCE VALUES IN ACCORDANCE WITH NFPA 1971-2018 EDITION. PERFORMED BY UNDERWRITERS LABORATORIES.
* TESTED AT PBI® LAB. ** NOMINAL VALUES.




6

TWO layers

ONE layer





For a proper fit, INNOTEX® GRAY™ particulate-blocking hoods are available in **2 sizes.** To determine yours, measure the circumference of your head above the ear.

SIZE	HEAD CIRCUMFERENCE (inches)		
M/L	Less than 23.5"		
XL	23.5" - 25"		



innotexprotection.com













