

# ONE AND DONE.



**INNO**TEX  
**ENERGY**<sup>™</sup>

HARNESSES & BELTS

 **INNO**<sup>®</sup>  
**TEX**

# READY WHEN YOU NEED IT, OUT OF THE WAY WHEN YOU DON'T.

## INNOTEX ENERGY™ INTEGRATED CLASS II HARNESS

The sturdy **Class II Harness** is integrated into our INNOTEX® ENERGY™ turnout pants between the outer shell and the liner system so it's immediately accessible when you need it and out of the way when you don't. Rigging the harness is as easy as donning the pants. One and done.

**Made of 100% Dupont™ Kevlar® webbing** with high-strength Kevlar® stitching and heavy-duty hardware for extreme durability. The harness system can be set up left-to-right or right-to-left, depending on your preference. Its hook-and-D closure ensures optimal speed and secure fastening.

The **extra-stable double-layered A-frame** is stowed on the waist belt and comes equipped with sliding D-rings for easy attachment to an escape system. Adjusters on the waist band and leg loops provide a customized fit for superior comfort. Loading the harness automatically brings the leg loops into the appropriate seating position. The entire harness can be quickly removed for easy care and maintenance.



GEMTOR™ 544 FR CLASS II HARNESS  
CLASSIFIED BY UNDERWRITERS LABORATORIES INC. IN ACCORDANCE WITH NFPA 1983-2017 57AF



**STABLE A-FRAME DESIGN**  
CARABINER NOT INCLUDED.

## FEATURES

- 1 Easy-opening hook & loop belt loops, front and back.
- 2 Sliding D-ring to attach an escape system.
- 3 Sliding D-ring to attach to a tether.
- 4 Leg loops.
- 5 Quick-release stow tab for tether.
- 6 Various pocket options to store rescue devices.  
Ex: 9" x 9" self-rescue pocket with Kevlar® and polymer-coated aramid available.  
Extra-large 10" x 10" cargo pocket is shown.
- 7 Pass-through opening.
- 8 Opening covered with outer shell fabric to prevent water from infiltrating the pants and to add structural integrity. Stress points are reinforced with bar tacks.

The integrated harness option is available in sizes 30 to 54 only. Comes with our neoprene-padded H-back suspenders that attach to horizontal loops, so there is no metal hardware to dig in or catch.



## INNOTEX® PREMIUM ESCAPE BELT

Designed to be worn on the turnout pants and to be adjustable to fit a large range of sizes.

The gross adjustment on the back of the belt allows the firefighter to adjust the belt to the rough size needed. It only takes a few minutes to adjust the gross adjuster, and once donned, the forward-pull fine adjustment strap allows the belt to be tightened or relaxed for a custom fit. The Premium Escape belt comes standard with one fixed D-Ring and one sliding D-Ring, both of which are NFPA Certified Attachment /Positioning points.

### FEATURES:

- Size: 28" – 50"
- Webbing: 1.75" 100% Kevlar®
- Buckles: Forged steel (Buckles & D-ring)
- Comes with 4 inches belt loops (6X)
- Certified NFPA 1983: 2017 Standard on Life Safety Rope and Equipment for Emergency Services
- Weight: 1.4 lbs ± 0.2 lbs
- Available for ENERGY only



## INNOTEX® ESCAPE BELT

Lightweight belt and easy to use with a single point adjustment feature that lets the firefighter quickly adjust to the proper fit. The Belt series has 1.75" nylon construction and comes standard with an attachment point for a bailout and/or connecting an NFPA ladder strap.

### FEATURES:

- Size: 28" – 42"
- Webbing: 1.75" 100% Nylon FR
- Hardware: Aluminum
- Comes with 4 inches belt loops (6X)
- Certified NFPA 1983: 2017 Standard on Life Safety Rope and Equipment for Emergency Services
- Lightweight belt: 0.6 lbs ± 0.2
- Available for ENERGY only



## INNOTEX® EXTERNAL CLASS II HARNESS

The INNOTEX® External Class II harness is worn externally over the turnout pants. It is available with lightweight Cobra aluminum buckles. The self-adjusting leg straps automatically tighten when the harness is used for rappelling. The harness fits a full range of sizes.

### FEATURES:

- Size: 28" – 42"
- Webbing: 1.75" & 1.25" 100% Kevlar®
- Hardware: Forged steel (Buckles & D-ring)
- Comes with 4 inches belt loops (6X) and 2 inside legs loops
- Certified NFPA 1983: 2017 Standard on Life Safety Rope and Equipment for Emergency Services
- Weight: 2.0 lbs ± 0.2 lbs
- Available for ENERGY only



[innotexprotection.com](http://innotexprotection.com)

DUPOINT  
**Kevlar** | **Nomex**



**GORE**<sup>®</sup>  
**CROSSTECH**<sup>®</sup>



 **TENCATE**

StedAlu  
**PREVENT**

**3M** | **Scotchlite**<sup>™</sup>  
Reflective Material

**INNOTEX<sup>®</sup> USA**

2397 Harts Ferry Road  
Ohatchee, AL 36271  
USA

**INNOTEX<sup>®</sup> CANADA**

275 Gouin Street  
Richmond (Quebec)  
Canada, J0B 2H0

**INNOTEX<sup>®</sup> CUSTOMER SERVICE**

1-888-821-3121 (U.S. & Canada)  
Tel: 819-826-5971  
Fax: 819-826-5195

© 2022 INNOTEX INC. PRODUCTS ARE DISTRIBUTED IN THE U.S.A. BY INNOTEX CORP. ALL RIGHTS RESERVED. TM, ® AND THE INNOTEX LOGO ARE REGISTERED TRADEMARKS OF INNOTEX. † ALL OTHER TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. INNOTEX RESERVES THE RIGHT AT ANY TIME TO DISCONTINUE OR CHANGE SPECIFICATIONS, PRICE, DESIGN, FEATURES, MODELS OR EQUIPMENT WITHOUT INCURRING ANY OBLIGATION. PRINTED IN CANADA

CHA0000000020EN